



## IWR AA Aluminium foil 1050 50 Soft

### Description

IWR AA Aluminium foil 1050 50 Soft is a 50 micron thick plain aluminium foil used to for a variety of applications. It is used to complete the vapour barrier system on slabs, pipe sections. It is also used to wrap pipe lines where heat tracing is used.

### Construction

1 layer of Aluminium Alloy AA1050 with a thickness of 50 microns. Other thicknesses available on request.

### Availability

500 mm(w) on rolls of appr. 20 kgs.  
1000 mm(w) on rolls of appr. 20 kgs.

### Packing

Foil is wound on aluminium tubes due to heat treatment of material.

### Applicable standard

DIN 1788; AA-9; NF a 50.471; EN 546-2

### Physical properties

Weight	135	gr/m <sup>2</sup>
--------	-----	-------------------

### Chemical properties

Min % Al	99,5	%
----------	------	---

IMPORTANT: Insu-W-Rapid BV warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. We make no other warranties and expressly disclaim any warranties of merchantability or fitness for a particular purpose. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. No guarantees for completeness, accuracy or results is expressed nor implied. The suitability of the product to an intended use is the sole responsibility of the user. Since material choice and application method are beyond our control, we accept no liability for direct or consequential damages.

Datasheet "IWR AA Aluminium foil 1050 50 Soft" – April 2012 – V1.0

INSU-W-RAPID BV, P.O. Box 3114, 5003 DC Tilburg, The Netherlands  
Industrial Estate De Sonman, De Sonman 15, 5066 GJ Moergestel, The Netherlands  
Telephone: +31 13 595 29 20, Fax: +31 13 595 29 21, E-mail: [sales@insu-w-rapid.nl](mailto:sales@insu-w-rapid.nl), [www.insu-w-rapid.nl](http://www.insu-w-rapid.nl)